

Fully adhered Liquid applied single-ply Membrane



A totally integrated roofing system comprising of factory produced roofing trims and accessories installed in conjunction with a GRP (glass reinforced polyester) **fully bonded and totally seamless** membrane applied in situ.

- Suitable for use on **most types of flat or low-pitched roofs.**
- **Cold applied.**
- **No maintenance required.**

The membrane is applied in a wet form allowing to easily incorporate the most **intricate roof detail and contours** into one integral and completely **seamless** roof covering.

The finished surface is highly durable and will easily withstand foot traffic, this makes it the ideal roof covering for **walkways, balconies and roof gardens.**



- A single homogenous material renowned for its long-term service, durability and resistance to weathering. The system carries a comprehensive **25 year guarantee.**
- The membrane finishes which are resin based top-coat act to reduce thermal transfer and add to the overall weathering resistance, there is no requirement for other solar reflection materials, gravel or chippings.
- The top-coats are available light or mid grey as standard or they can be supplied in a selection of colour choice to order. An alternative finish is to incorporate a slip free, slate granular surface.



Technical data

The Membrane

Weight: 2.5 k/m²

Polyester resin to BS 3532

Lloyd's register approval
certificate No mats/3476/1

Fibreglass reinforcement

600gsm to BS 3946

Lloyd's register approval
certificate No mats/3551/1

Polyester top coat to BS 2782

Lloyd's register approval
certificate No mats/3476/1

Fire Grade

Class 3 & 7 to BS 476 part 3

Installation

Supply and installation by trained and
accredited contractors.

The components

A complete range of components
manufactured to complement the system,
edge trims, deck to wall fillets, water
chutes, rainwater outlets, pipe covers
and most accessories (see S.R.S. product
range literature).

Approvals and Quality

All S.R.S. Easy Fit Products and
accessories are manufactured
under factory conditions utilising GRP
production equipment that
ensures a controlled product of
consistent quality and reliability.
Only 1st quality S.R.S. resins and glass
fibre reinforcement form the membrane.

